Product Specifications

SEDIA CHAIR - SS 803

CONSTRUCTION

- All corners are strengthened with screwed and glued hardwood blocks.
- Birch frame is assembled with mortise and tenon joints and glued.
- Seat made of ¾" plywood with elastic webbing and covered with 3" medium-compression Velva foam.
- Back rest made of hardwood with elastic webbing and covered with 3" low-compression Velva foam.
- Sides of cushions covered with ½" low-compression Celcor foam.
- Birch armrests.
- Nylon glides under the legs.
- Single top stitching maintains tissue nestles.

FINISHES

- Customers can choose an upholstery or vinyl from the supplier of their choice.
- Choice of 26 wood stains.

DIMENSIONS

Overall dimensions: 22"w x 22¾"d x 33"h

Seat dimensions: 19½"w x 18"d x 17½"h

Armrest height: 25"

COM YARDAGE REQUIRED

Yardage: 2

OPTIONS

- Double top stitching or decorative piping.
- Flammability technical bulletin CAL133.
- Models presented are suggestions: they can be customized to meet individual needs.

MANUFACTURER'S FEATURES

- The foam used meets or exceeds the California Technical Bulletin 117 requirements.
- Five-year warranty against manufacturing defects and on the wooden frame.
- Products are manufactured in North America.

logiflex